

DesignLite range with DL.CLS.L6.15.6W



LUXO 6 —Down Light


Replaces:

: 35W Metal Halide; 75W Halogen

Applications:


Retail, Commercial & Architectural Illumination

Warranty (Yrs.)

3



- 15,4 Watt module can replace a 75Watt halogen source, 36 Watt TC-L, 35 Watt HQI.
- High quality easy interchangeable lens optics in different beam angles; 25°, 40°, 60° and 120°.
- Massive aluminum CNC cut housing for optimal cooling.
- Optional diffusion filter for very soft light dispersion available.
- Each module is horizontally and vertically adjustable.
- Round-, square-, dual, triple and quad mounting plate available.
- Dimming possible.
- CLS SmartConnect system.



Finish	Steel
IP Rating	40
System Power (W)	15.6
Input Voltage (V)	200—277 V AC
Input frequency (Hz)	50/60
Power Factor (cos phi)	>0.95
Operating temp. (°C)	10 ~ 40
Storage temp. (°C)	0 ~40
Weight (gr)	450
Dimensions (mm): LxWxH	126 x dia x 60

Beam Angle (°FWHM)	25, 40, 60, 120,
Flux (Lm)	1350lm dimmable
CRI (Ra4)	85
CCT (K)	2700K, 3000K, 4000K
Life Expectancy (Hrs.)	50,000

