

## DesignLite range with DL.CLS.UG.20W



### Ultima—Architectural Gallery Track Light


**Replaces:**

: 35W Metal Halide; 100W Halogen

**Applications:**

Museums, Galleries, Architectural Illumination

**Warranty (Yrs.)**

3



- Easy dimming per fixture via potentiometer on the housing.
- Energy savings up to 80% in comparison with traditional light sources such as halogen, T5 and CFL.
- Light output up to 1800 lumen with a power consumption of only 20 Watts.
- Adjust the look of fixtures to the interior design: the housing of the Ultima series is available in many colours.
- Beam angles available from 8° to 54°, the Ultima is therefore suitable for both low and high ceilings.
- Remarkably good colour rendition, CRI > 85.
- 'Single Bin' LED technology. Annoying colour variations in appearance of white light, such as was often the case with metal halide, CFL and T5 luminaires, now belong to the past. The result is a uniform and consistent lighting scheme.

Finish	White, Grey, Black Powder coat	Beam Angle (°FWHM)	8, 12, 30, 54, 12x46
IP Rating	40	Flux (Lm)	1800lm adjustable
System Power (W)	20	CRI (Ra4)	85
Input Voltage (V)	200—277 V AC	CCT (K)	2700K, 3000K, 4000K, 5000K
Input frequency (Hz)	50/60	Life Expectancy (Hrs.)	50,000
Power Factor (cos phi)	>0.95		
Operating temp. (°C)	10 ~ 40		
Storage temp. (°C)	0 ~40		
Weight (gr)	1200		
Dimensions (mm): LxWxH	180 x 180 x 246		

