

DesignLite range with DL.CLS.US.20W



Ultima—Surface mount light



Replaces:

: 35W Metal Halide; 100W Halogen

Applications:

Retail, Commercial & Architectural Illumination

Warranty (Yrs.)

3



- The Ultima S is the surface mounted version of the Ultima with an integrated driver in the housing— phase dimmable, 1-10 Volt dimmable and non dimmable
- Energy savings up to 80% in comparison with traditional light sources such as halogen, T5 and CFL.
- Light output up to 1800 lumen with a power consumption of only 20 Watts. CRI > 85.
- Adjust the look of fixtures to the interior design: the housing of the Ultima series is available in many colours.
- Beam angles available from 8° to 54°, the Ultima is therefore suitable for both low and high ceilings.
- Can be used as a built in or semi built up fixture with a sophisticated 'side glow' effect.
- Anti glare design with a very good URG score.

Finish	White, Grey, Black Powder coat	Beam Angle (°FWHM)	8, 12, 30, 54, 12x46
IP Rating	40	Flux (Lm)	1800lm dimmable
System Power (W)	20	CRI (Ra4)	85
Input Voltage (V)	200—277 V AC	CCT (K)	2700K, 3000K, 4000K, 5000K
Input frequency (Hz)	50/60	Life Expectancy (Hrs.)	50,000
Power Factor (cos phi)	>0.95		
Operating temp. (°C)	10 ~ 40		
Storage temp. (°C)	0 ~40		
Weight (gr)	1200		
Dimensions (mm): LxWxH	180 x 180 x 74		

