

# DesignLite- DL.J4.5008.018AC

## Anular Architectural Pendant Downlight


**Replaces:**

22W T9 circular Fluorescent

**Applications:**

Retail &amp; Display, Office, Educational &amp; Communal, as well as General installations

**Warranty (Yrs.)**

5



DesignLite-J4.5008 is a high brightness, Anular Architectural Pendant Downlight which replaces a 22W T9 circular fluorescent fixture. Producing 1250lm, this energy saving and maintenance free light is brighter, cheaper to run and more environmentally friendly than its traditional fluorescent predecessors.

Available in 3000K / 4000K / 5000K Kelvin colour temperatures, the J4.5008 is ideal in Retail & Display, Office, Educational & Communal, as well as General applications. The amazingly uniform light field has none of the glare often associated with LED point source lights.

DesignLite-J4.5008's output is inherently stable and therefore does not shift or fade during a typical lifetime of 10 years in a commercial environment. DesignLite is simple to install and strikingly elegant in looks.

Complete with Analogue (1-10V) interface.

IP Rating	20	Beam Angle (°FWHM)	120
System Power (W)	18	Flux (Lm)	1250
System efficacy (Lm/W)	69	CRI (Ra4)	80
Input Voltage (V)	120-277V AC	CCT (K)	3000K / 4000K / 5000K
Input frequency (Hz)	50/60	Life Expectancy (Hrs.)	50000
Power Factor (cos phi)	0.9	Lx @ 1m	1,100
Operating temp. (°C)	-10 ~ 35	2m	550
Storage temp. (°C)	0 ~ 35	3m	367
Weight (gr)	1500	Illuminated area (m)@ 1m	1.91
Dimensions (mm): LxWxH	500x 0x 8	2m	3.82
		3m	5.73