

Emergency Pack - EP.NM.3E0EN

3 W Emergency pack


Replaces:

: 20W Halogen

Applications:

Retail & Display, Office, Educational & Communal, Industrial, Warehousing & Distribution as well as General installations

Warranty (Yrs.)


The EP.NM.3E0EN 3W emergency LED downlight is suitable for applications in which emergency lighting is required, including retail spaces, office and corridors.

This downlight uses a NiMH battery pack to provide a 3 hour duration of emergency lighting should the power be cut and requires 24 hours to fully charge.

It features a recessed mounting bracket and an efficient reflector design.

IP Rating	20	Beam Angle (°FWHM)	120
System Power (W)	3	Flux (Lm) / Ballast Lumen Factor	190
System efficacy (Lm/W)	63	CRI (Ra4)	>60
Input Voltage (V)	200~240Vac	CCT (K)	6500K
Input frequency (Hz)	50	Life Expectancy (Hrs.)	> 50000
Power Factor (cos phi)	>0.7	Lx @ 1m	20
Operating temp. (°C)	-20 ~ 35	2m	5
Storage temp. (°C)	0 ~ 35	3m	2
Weight (gr)		Illuminated area (m)@ 1m	9.42
Dimensions (mm): LxWxH	0x 0x 0	2m	37.68
		3m	84.78