

## Hydra- HY.D.064ST

Rectangular, dual headed, swiveled downlight

**Replaces:**

: 2 x 50W CDM Metal Halide : 400W Halogen

**Applications:**

Retail & Display, Office, Educational & Communal, as well as General installations

**Warranty (Yrs.)**

5



Hydra D.064 is a Rectangular, dual headed, swiveled downlight, designed for Retail & Display, Office, Educational & Communal, as well as General illumination to replace 2 x 50W CDM Metal Halide and 400W Halogen luminant(s).

With a minimum light output of 4700lm, this luminaire is a simple replacement for existing recessed lighting systems. The high efficacy (73Lm/W) light engine has the power to illuminate display bays and cabinets with a similar effect to a Metal Halide lamp rated 2 x 50W CDM.

The active cooling systems allows the luminaire to be placed inside a closed cavity and maintains a very low operating temperature extending the life and improving the performance of the luminaire. D.064 has a useful life of 10 years in a retail environment, unlike metal halide which has an operating life of around 3 years. D.064's colour does not deteriorate with age.

IP Rating	20	Beam Angle (°FWHM)	60E
System Power (W)	64	Flux (Lm)	4700
System efficacy (Lm/W)	73	CRI (Ra4)	>80
Input Voltage (V)	100- 240v	CCT (K)	3000K / 4000K / 5000K
Input frequency (Hz)	50/60	Life Expectancy (Hrs.)	> 50000
Power Factor (cos phi)	>0.9	Lx @ 1m	3,133
Operating temp. (°C)	10 ~ 40	2m	783
Storage temp. (°C)	0 ~40	3m	348
Weight (gr)		Illuminated area (m)@ 1m	1.50
Dimensions (mm): LxWxH	340x 180x 70	2m	6.00
		3m	13.50