

## NOVA PaneLite- NP .J3.1215.028AC

LED lay-in panel



### Replaces:

1x 36W Fluorescent

### Applications:

Retail & Display, Office, Educational & Communal, as well as General installations

### Warranty (Yrs.)

5



NOVA PaneLite-J3.1215 is a high brightness , dimmable LED panel which replaces a 1200mm x 150 mm fluorescent ceiling fixture. Producing 1586lm, this energy saving and maintenance free light is brighter, cheaper to run and more environmentally friendly than its traditional T8 or T5 fluorescent predecessors.

Available in 3500K / 5500K Kelvin colour temperatures, the J3.1215 is ideal in Retail & Display, Office, Educational & Communal, as well as General applications. The amazingly uniform light field has none of the glare often associated with LED point source lights.BI559:BI580

NOVA PaneLite-J3.1215's output is inherently stable and therefore does not shift or fade during a typical lifetime of 10 years in a commercial environment. NOVA PaneLite is simple to install and strikingly elegant in looks.

Complete with Analogue (1-10V) interface.

IP Rating	20	Beam Angle (°FWHM)	120
System Power (W)	28	Flux (Lm)	1586
System efficacy (Lm/W)	57	CRI (Ra4)	75
Input Voltage (V)	Direct 230 V [Line] power	CCT (K)	3500K / 5500K
Input frequency (Hz)	50 - 60	Life Expectancy (Hrs.)	40000
Power Factor (cos phi)	0.9	Lx @ 1m	547
Operating temp. (°C)	-20 ~ 35	2m	137
Storage temp. (°C)	0 ~ 35	3m	61
Weight (gr)	2900	Illuminated area (m)@ 1m	2.25
Dimensions (mm): LxWxH	1200x 150x 43	2m	9.00
		3m	20.25