

## NOVA PaneLite- NP .J3.1230.055AC

LED lay-in panel



### Replaces:

2x 36W Fluorescent

### Applications:

Retail & Display, Office, Educational & Communal, as well as General installations

### Warranty (Yrs.)

5



NOVA PaneLite-J3.1230 is a high brightness , dimmable LED panel which replaces a 1200mm x 300 mm fluorescent ceiling fixture. Producing 3375lm, this energy saving and maintenance free light is brighter, cheaper to run and more environmentally friendly than its traditional T8 or T5 fluorescent predecessors.

Available in 3500K / 5500K Kelvin colour temperatures, the J3.1230 is ideal in Retail & Display, Office, Educational & Communal, as well as General applications. The amazingly uniform light field has none of the glare often associated with LED point source lights.BI559:BI580

NOVA PaneLite-J3.1230's output is inherently stable and therefore does not shift or fade during a typical lifetime of 10 years in a commercial environment. NOVA PaneLite is simple to install and strikingly elegant in looks.

Complete with Analogue (1-10V) interface.

IP Rating	20	Beam Angle (°FWHM)	120
System Power (W)	55	Flux (Lm)	3375
System efficacy (Lm/W)	61	CRI (Ra4)	75
Input Voltage (V)	Direct 230 V [Line] power	CCT (K)	3500K / 5500K
Input frequency (Hz)	50 - 60	Life Expectancy (Hrs.)	40000
Power Factor (cos phi)	0.9	Lx @ 1m	1,170
Operating temp. (°C)	-20 ~ 35	2m	293
Storage temp. (°C)	0 ~ 35	3m	130
Weight (gr)	4900	Illuminated area (m)@ 1m	2.25
Dimensions (mm): LxWxH	1200x 300x 43	2m	9.00
		3m	20.25