

## NOVA PaneLite- NP . J3.2023.018ST

Circular LED lay-in panel


**Replaces:**

22 W T9 circular Fluorescent

**Applications:**

Retail & Display, Office, Educational & Communal, as well as General installations

**Warranty (Yrs.)**

5



NOVA PaneLite-J3.2023 is a high brightness, Circular LED lay-in panel which replaces a 22 W T9 circular fluorescent ceiling fixture. Producing 725lm, this energy saving and maintenance free light is brighter, cheaper to run and more environmentally friendly than its traditional fluorescent predecessors.

Available in 3500K / 5500K Kelvin colour temperatures, the J3.2023 is ideal in Retail & Display, Office, Educational & Communal, as well as General applications. The amazingly uniform light field has none of the glare often associated with LED point source lights.

NOVA PaneLite-J3.2023's output is inherently stable and therefore does not shift or fade during a typical lifetime of 10 years in a commercial environment. NOVA PaneLite is simple to install and strikingly elegant in looks.

IP Rating	20	Beam Angle (°FWHM)	120
System Power (W)	18	Flux (Lm)	725
System efficacy (Lm/W)	40	CRI (Ra4)	75
Input Voltage (V)	Direct 230 V [Line] power	CCT (K)	3500K / 5500K
Input frequency (Hz)	50 - 60	Life Expectancy (Hrs.)	40000
Power Factor (cos phi)	0.9	Lx @ 1m	250
Operating temp. (°C)	-20 ~ 35	2m	63
Storage temp. (°C)	0 ~ 35	3m	28
Weight (gr)	4900	Illuminated area (m)@ 1m	9.42
Dimensions (mm): LxWxH	200x 0x 23	2m	37.68
		3m	84.78