

NOVA PaneLite- NP.J3.6015.018AC

LED lay-in panel



Replaces:

1x 18W Fluorescent

Applications:

Retail & Display, Office, Educational & Communal, as well as General installations

Warranty (Yrs.)

5



NOVA PaneLite-J3.6015 is a high brightness, dimmable LED panel which replaces a 600mm x 150 mm fluorescent ceiling fixture. Producing 1128lm, this energy saving and maintenance free light is brighter, cheaper to run and more environmentally friendly than its traditional T8 or T5 fluorescent predecessors.

Available in 3500K / 5500K Kelvin colour temperatures, the J3.6015 is ideal in Retail & Display, Office, Educational & Communal, as well as General applications. The amazingly uniform light field has none of the glare often associated with LED point source lights. BI559:BI580

NOVA PaneLite-J3.6015's output is inherently stable and therefore does not shift or fade during a typical lifetime of 10 years in a commercial environment. NOVA PaneLite is simple to install and strikingly elegant in looks. Complete with Analogue (1-10V) interface.

IP Rating	20	Beam Angle (°FWHM)	120
System Power (W)	18	Flux (Lm)	1128
System efficacy (Lm/W)	63	CRI (Ra4)	75
Input Voltage (V)	Direct 230 V [Line] power	CCT (K)	3500K / 5500K
Input frequency (Hz)	50 - 60	Life Expectancy (Hrs.)	40000
Power Factor (cos phi)	0.9	Lx @ 1m	396
Operating temp. (°C)	-20 ~ 35	2m	99
Storage temp. (°C)	0 ~ 35	3m	44
Weight (gr)	2300	Illuminated area (m)@ 1m	2.25
Dimensions (mm): LxWxH	600x 150x 43	2m	9.00
		3m	20.25