

Nova Panelite- NP.J6.5959.037STS

LED lay-in panel



Replaces:

4 x 18W Fluorescent

Applications:

Retail & Display, Office, Educational & Communal, as well as General installations

Warranty (Yrs.)

3



Nova Panelite-J6.5959 is a high brightness emergency supported backlit LED tile which replaces a 4 x 18W recessed fluorescent ceiling fixture. Producing 3200lm, this energy saving and maintenance free light is brighter, cheaper to run and more environmentally friendly than its traditional T8 or T5 fluorescent predecessors.

Available in 4000K / 5000K Kelvin colour temperatures, the J6.5959 is ideal in Retail & Display, Office, Educational & Communal, as well as General applications. The light field is modified by a specially designed diffusor and has none of the glare often associated with LED point source lights.

Nova Panelite-J6.5959's output is inherently stable and therefore does not shift or fade during a typical lifetime of 10 years in a commercial environment. Nova Panelite is simple to install and virtually maintenance free. Complete with Emergency Supported interface.

IP Rating	20
System Power (W)	36.5
System efficacy (Lm/W)	88
Input Voltage (V)	115~240Vac
Input frequency (Hz)	50 - 60
Power Factor (cos phi)	>0.9
Operating temp. (°C)	-20 ~ 35
Storage temp. (°C)	0 ~ 35
Weight (gr)	4300
Dimensions (mm): LxWxH	295x 295x 100

Beam Angle (°FWHM)	100
Flux (Lm) / Ballast Lumen Factor	3200/0.05
CRI (Ra4)	>80
CCT (K)	4000K / 5000K
Life Expectancy (Hrs.)	50000
Lx @ 1m	1,390
2m	348
3m	154
Illuminated area (m)@ 1m	4.45
2m	17.80
3m	40.05