



Family	Part number (In)	Description	Application								Replaces			Correlated Colour Temperature					Shell Colour											
			Retail & Display	Office, Educational & Communal	General	Input Voltage	Power Factor	Luminaire Lumen	Luminaire Power	Luminaire Efficacy	UGR	Mercury vapour	Metal Halide	Halogen	3000K	4000K	5000K	Colour Rendering Index	LED Life (LM70)	RAL9005 [Jet Black]	Brushed Steel	RAL9016 [Signal White]	Bespoke RAL [upon request]	Housing Material	IP Rating	Dimensions Length/Width/Height	Weight unpacked	Marking	Supply Connection	
BayLite	BA.C.067ST	Circular recessed swivel head downlight	●		●	100-240v	>0.9	4850 lm	67 w	72 lm/w			140W	>70W	400W	●	●	●	>80	> 50000	●	●	●	●	Steel	20	150xdiax75	850	CE	LNE (240V)
BayLite	BA.R.067ST	Rectangular recessed swivel head downlight	●		●	100-240v	>0.9	4850 lm	67 w	72 lm/w			140W	>70W	400W	●	●	●	>80	> 50000	●	●	●	●	Steel	20	172x125x75	850	CE	LNE (240V)
BayLite	BA.C.048ST	Circular recessed swivel head downlight	●	●	●	100-240v	>0.9	3500 lm	48 w	73 lm/w			100W	70W	300W	●	●	●	>80	> 50000	●	●	●	●	Steel	20	150xdiax75	800	CE	LNE (240V)
BayLite	BA.R.048ST	Rectangular recessed swivel head downlight	●	●	●	100-240v	>0.9	3500 lm	48 w	73 lm/w			100W	70W	300W	●	●	●	>80	> 50000	●	●	●	●	Steel	20	172x125x75	800	CE	LNE (240V)
BayLite	BA.C.032ST	Circular recessed swivel head downlight	●	●	●	100-240v	>0.9	2350 lm	32 w	73 lm/w			70W	50W	200W	●	●	●	>80	> 50000	●	●	●	●	Steel	20	150xdiax75	750	CE	LNE (240V)
BayLite	BA.R.032ST	Rectangular recessed swivel head downlight	●	●	●	100-240v	>0.9	2350 lm	32 w	73 lm/w			70W	50W	200W	●	●	●	>80	> 50000	●	●	●	●	Steel	20	172x125x75	750	CE	LNE (240V)
BayLite	BA.US.032ST	Undershelf fixed head downlight	●			100-240v	>0.9	2350 lm	32 w	73 lm/w			70W	50W	200W	●	●	●	>80	> 50000	●	●	●	●	Steel	20	1000x150x75	1000	CE	LNE (240V)
BayLite	BA.BZ1	Glass Bezel Accessory	●	●	●	N/A	N/A	N/A	N/A	N/A	●													N/A		70xdiax80	200	N/A		