Family	Part number (in)	Description	Application	Retail & Display	Office, Educational & Communal	Industrial, Warehousing & Distribution	General	Input Voltage	Power Factor	Luminaire Lumen	Luminaire Power	Luminaire Efficacy	Replaces	Fluorescent	Metal Halide	Halogen	Corolated Colour Temperature	2700K	3000K	4000K	5000K	6500K	Colour Rendering Index	LED Life (L.M70)	Shell Colour	RAL9005 [Jet Black]	Brushed	RAL9016 [Signal White]	Bespoke RAL [upon request]	Housing Material	IP Rating	Dimensions Length/Width/Height	Weight unpacked	Marking	Supply Connection
TapeLite	TL.12.7E0ST	LED Flexible Strip		●			●	12 V DC	>0.9	600 lm	7 w	86 lm/w				50W			●		6K		>70	> 50000						Plastic	65	1x50x3.5		CE	LNE (240V)
TapeLite	TL.24.014ST	LED Flexible Strip		●			●	24 V DC	>0.9	1150 lm	14 w	82 lm/w				2 x 50W			●		6K		>70	> 50000						Plastic	65	1x50x3.5		CE	LNE (240V)
BritePuck	BP.12VAC.3E0ST	Under Cabinet Puck Pight					●	12V AC	>0.9	150 lm	3 w	50 lm/w				G4 20W		●	●	●	●		>80	> 50000		●	●	●	●	Aluminium	20	DIA 70 by 10	300	CE	LNE (240V)
LobbyLite	LO.3.043ST	Hall and Lobby replacment lamp			●	●	●	12V AC	>0.9	2200 lm	43 w	51 lm/w		2x 18W PL2					●	●	●		>80	> 50000			●			Aluminium	20			CE	LN(12V AC)
Emergency Pack	EP.NM.1E0EN	1 W Emergency pack		●	●	●	●	220V AC	>0.7	60 lm	1 w	60 lm/w				10W						●	>60	> 50000						Aluminium	20			CE	LNE (240V)
Emergency Pack	EP.NM.3E0EN	3 W Emergency pack		●	●	●	●	200~240Vac	>0.7	190 lm	3 w	63 lm/w				20W						●	>60	> 50000						Aluminium	20			CE	LNE (240V)