



Family	Part number (in)	Description	Application			Input Voltage	Power Factor	Luminaire Lumen	Luminaire Power	Luminaire Efficacy	Replaces			Correlated Colour Temperature			Colour Rendering Index	LED Life (LM70)	Shell Colour		RAL9005 [Jet Black]	Brushed Steel	RAL9016 [Signal White]	Bespoke RAL [upon request]	Housing Material	IP Rating	Dimensions Length/Width/Height	Weight unpacked	Marking	Supply Connection
			Retail & Display	Office, Educational & Communal	General						Fluorescent	Metal Halide	Halogen	3000K	4000K	5000K			RAL9005 [Jet Black]	Brushed Steel										
Hydra	HY.S.032ST	Square, solo headed, swiveled downlight	•	•	•	100-240v	>0.9	2350 lm	32 w	73 lm/w		1 x 50W CDM	200W	•	•	•	>80	> 50000	•	•	•	•	Steel	20	180x180x70		CE	LNE (240V)		
Hydra	HY.D.064ST	Rectangular, dual headed, swiveled downlight	•	•	•	100-240v	>0.9	4700 lm	64 w	73 lm/w		2 x 50W CDM	400W	•	•	•	>80	> 50000	•	•	•	•	Steel	20	340x180x70		CE	LNE (240V)		
Hydra	HY.T.096ST	Rectangular, tri headed, swiveled downlight	•	•	•	100-240v	>0.9	6950 lm	96 w	72 lm/w		3 x 50W CDM	600W	•	•	•	>80	> 50000	•	•	•	•	Steel	20	500x180x70		CE	LNE (240V)		
Hydra	HY.Q.128ST	Square, Quad headed, swiveled downlight	•	•	•	100-240v	>0.9	9300 lm	128 w	73 lm/w		4 x 50W CDM	800W	•	•	•	>80	> 50000	•	•	•	•	Steel	20	340x340x70		CE	LNE (240V)		
Hydra DS	HM.DS.035ST	Circular drop & swivel downlight	•	•	•	100-240v	>0.9	3100 lm	35 w	89 lm/w		50W CDM	300W	•	•	•	>80	> 50000			•		Plastic	20			CE	LNE (240V)		
Hydra DS	HM.DS.018ST	Circular drop & swivel downlight	•	•	•	100-240v	>0.9	1550 lm	18 w	86 lm/w		25W CDM	100W	•	•	•	>80	> 50000			•		Plastic	20			CE	LNE (240V)		
Hydra	HY.C.012ST	Circular recessed swivel head downlight	•	•	•	100-240v	>0.9	900 lm	12 w	75 lm/w			50W	•	•	•	>80	> 50000	•	•	•	•	Steel	20	70xdiax80		CE	LNE (240V)		
Hydra	HY.C.012TE	Circular recessed swivel head 12V AC downlight	•	•	•	12V AC	>0.9	800 lm	12 w	67 lm/w			50W	•	•	•	>80	> 50000	•	•	•	•	Steel	20	70xdiax80		CE	LN(12VAC)		
Hydra	HY.C.033ST	Circular recessed downlight	•	•	•	100-240v	>0.9	3100 lm	33 w	94 lm/w		2 x 26w PL	50W CDM	300W	•	•	•	>80	> 50000			•		Alum	20	180xdiax80	1070	CE	LNE (240V)	
Hydra	HY.C.022ST	Circular recessed downlight	•	•	•	100-240v	>0.9	2050 lm	22 w	93 lm/w		2 x 18W PL	35W CDM	200W	•	•	•	>80	> 50000			•		Alum	20	230xdiax120	670	CE	LNE (240V)	