



Family	Part number (in)	Description	Application							Replaces	Metal Halide	Correlated Colour Temperature			Shell Colour					
			Industrial, Warehousing & Distribution	General	Input Voltage	Power Factor	Luminaire Lumen	Luminaire Power	Luminaire Efficacy			52000K	Colour Rendering Index	LED Life (LM70)	RAL9005 [Jet Black]	Housing Material	IP Rating	Dimensions Length/Width/Height	Weight unpacked	Marking
AreaLux	A.AL360.1K4ST	Large Area LED Floodlighting	●	●	370 - 430 V AC	>0.95	109350 lm	1421 w	77 lm/w	2200W	●	80	60000	●	Steel	65	690x570x595	27000	CE	400V 3 Phase AC
AreaLux	A.AL.1K5ST	Large Area LED Floodlighting	●	●	370 - 430 V AC	>0.95	115450 lm	1500 w	77 lm/w	2200W	●	80	60000	●	Steel	65	690x570x595	27000	CE	400V 3 Phase AC
AAALux	A.WS.1K5ST	Dynamic LED sports floodlighting	●	●	370 - 430 V AC	>0.95	115450 lm	1500 w	77 lm/w	2200W	●	80	60000	●	Steel	65	690x570x596	27000	CE	400V 3 Phase AC
AreaLux	A.SB.0E0ST	Switch Box	●	●	370 - 430 V AC	>	lm	w	lm/w	2200W				●	Steel	65		0	CE	LNE (240V)
AreaLux	A.CB.0E0ST	ControlBox	●	●	370 - 430 V AC	>	lm	w	lm/w	2200W				●	Steel	65		0	CE	LNE (240V)