



Family	Part number (in)	Description	Application		Input Voltage	Power Factor	Luminaire Lumen	Luminaire Power	Luminaire Efficacy	Replaces	Fluorescent	Correlated Colour Temperature	3000K	4000K	5000K	Colour Rendering Index	LED Life (LM70)	Shell Colour		Aluminium	Housing Material	IP Rating	Dimensions Length/Width/Height	Weight unpacked	Marking	Supply Connection
			Retail & Display	General														Aluminium	Aluminium							
VisiLite	VI.L450.017ST	Linear Strip light	●	●	220-240v	>0.9	1100 lm	17 w	65 lm/w		1 x 18W T8		●	●	●	>80	> 50000	●	Aluminium	20	450x20x11		CE	Flying lead		
VisiLite	VI.L550.021ST	Linear Strip light	●	●	220-240v	>0.9	1350 lm	21 w	64 lm/w		1x 24W T5		●	●	●	>80	> 50000	●	Aluminium	20	550x20x11		CE	Flying lead		
VisiLite	VI.L900.036ST	Linear Strip light	●	●	220-240v	>0.9	2300 lm	36 w	64 lm/w		3 x 18W T8		●	●	●	>80	> 50000	●	Aluminium	20	900x20x11		CE	Flying lead		
VisiLite	VI.L1100.044ST	Linear Strip light	●	●	220-240v	>0.9	2900 lm	44 w	66 lm/w		2 x 36W T8		●	●	●	>80	> 50000	●	Aluminium	20	1100x20x11		CE	Flying lead		
Control Gear	CG.ET 12VAC.070ST	Electronic Transformer			220-240v	>0.9		44 w									> 50000		Plastic	20		150	CE	Flying lead		